

*“The Freefoam Colour Range offers short lead times, a highly durable product and gives us the closest match to our coloured window frames. Our research concluded that Colormax is the right commercial decision for us.”*

*Taylor Wimpey, Southern Division*



www.freefoam.com  
sales@freefoam.com

Central Commercial Park  
Centre Park Road  
Cork  
IRELAND  
T 021 496 6311  
F 021 496 5273

77-83 St James Mill Road  
Northampton  
NN5 5JP  
UK  
T 01604 591 110  
F 01604 580 299



\* Refers to white roofline and trims only

August 2015



## Plastops Fixings

- **Coloured Tops**  
To match all Freefoam products
- **High Shock Absorption**  
Plastops remain in place during fixing
- **A4 Marine Grade Stainless Steel**  
Eliminates rust and discolouration around pin; and they're tougher too
- **Ringshanked**  
For increased grip when installed
- **50 Year Extended Guarantee**  
Available on registered Installations
- **Belt Clip**  
Easy carrying and access to pins while you work
- **Durable Waterproof Packaging**  
Withstands rough on-site and transportation handling

## Colours



## Care & Installation of Coloured Products

When handled, stored and installed correctly, coloured profiles will remain 'fit for purpose' throughout the guarantee period.

### Handling & Storage

- Coloured products should be stored internally away from direct sunlight in their protective sleeving until just before installation.
- Never store coloured products externally or on top of vans for any length of time as heat distortion may occur.

### Installation

- Freefoam recommends the use of Plastops plastic-headed pins and nails for the installation of roofline products. Fixing centres vary but should never exceed 600mm for white profiles, 300mm for black profiles, and 400mm for other coloured and woodgrain profiles.
- Products should not be installed where ambient temperatures are likely to exceed 40 degrees Celsius, such as in close proximity to boiler flues or where there is reflected or radiated solar or other sources of heat. They should only be installed when the external air temperature is between 0 and 30 degrees Celsius. The thermal movement that occurs between day and night, sun and cloud, winter and summer should be allowed for as described in the installation recommendations.
- Hollow rigid products should be installed only in areas shaded from direct sunlight such as soffits, porch ceilings, internal cladding, etc. Hollow rigid profiles are not guaranteed for external cladding applications.
- Remove the protective film immediately after installation.
- General installation guidelines are outlined in our Technical & Specification Manual (call your local number at the back of this leaflet for a copy or download from www.freefoam.com).

### Notes:

1. The advice and recommendations in this and other technical documents applies only to standard installations and layouts. The user is in all cases recommended to consult with their Architect or Engineer.
2. All specifications, dimensions, descriptions and illustrations contained in any sales literature, quotation, or pricelist or other advertisement matter are intended merely to present a general idea of the goods that we sell. We reserve the right from time to time to make changes which are required to comply with any applicable safety or statutory requirements or which do not materially affect the quality or fitness for purpose of the goods you purchase from us.



## Colour Roofline Range



Freefoam - the colour specialists



# Colour Range

Freefoam's unique colour Roofline Range with Colormax® technology

Freefoam is the colour specialist. Freefoam manufacture one of the most technologically advanced self coloured PVC-U and PVC-UE fascia and soffit ranges using the unique patented Colormax® technology.

The ideal solution for architects, specifiers, contractors, Local Authorities and Housing Associations offering a wide range of ten standard colours, with guaranteed colour matching and colourfastness. The range is subject to industry leading guarantees of 50 years on white products\* and 10 years on all other colours.

Most importantly for the commercial sector the Colormax® technology allows Freefoam to supply the range with short lead times and minimal order quantities with many colours being available straight from stock.

For larger projects Freefoam also offer the flexibility to colour match specific shades or RAL equivalents to other elements of the build such as windows and doors.

\* Terms & conditions apply (see [www.freefoam.com](http://www.freefoam.com) for details)




The innovative Colormax® technology is unique to Freefoam

### INFINITY AND BEYOND!

Using a proprietary formulation that contains a unique selection of stabilisers and pigments specially chosen for their high colourfast properties, the Colormax technology means Freefoam can confidently offer an infinite range of colours\*.

### THE PROCESS

Freefoam manufacture using the co-extrusion process. A strong PVC-UE foam 'core' simultaneously co-extruded with a protective top coating of rigid PVC-U skin, creating a smooth, strong & hard wearing surface. A technically advanced master-batching process is used where a special blend of natural PVC compound is dosed on the extrusion line with specific concentrates of pigment.



\* Subject to minimum order quantities

## Colour Range

		
White Nearest RAL No. 9003	Pale Gold (PG) 1013	Sable (SAB) 1015
		
Storm Grey (SG) Nearest RAL No. 7045	Dark Grey (DG) 7015	Anthracite Grey (AG) 7016
		
Black (BL) Nearest RAL No. 9005	Regal Blue (RB) 5011	Rustic Green (GREEN) 6009
		
Leather Brown (LB) Nearest RAL No. 8017		

### Notes:

1. The RAL numbers shown above are the nearest to our colours however we cannot guarantee an exact match.
2. Colours shown are for availability identification only. Please see colour swatch or product samples for exact colour representations.
3. A wider colour range is available for special projects and a colour matching service is available subject to lead-time and minimum order quantities.
4. A full range of matching Plastops pins and nails is available.
5. Please contact Freefoam or see our Technical & Specification Manual for nearest NCS and Pantone reference numbers.

# Woodgrain Range

An extensive range of woodgrain roofline products including fascia, soffit, architrave, window trims, mouldings, Tudor board and cladding in a wide choice of traditional and contemporary colours.

Manufactured to last using marketing leading Renolit Exofol MX foil featuring built in Solar Shield Technology (SST) allowing Freefoam to offer a ten year guarantee on all foiled products.

- Built in sun reflection
- Reduced heat absorption
- Reduced profile temperature and expansion



		
Mahogany (WGM)	Light Oak (WGO)	Black Ash (WGB)
		
Rosewood (WGR)	Irish Oak (WGI)	Anthracite Grey (WGAG)
		
Cream (WGCR)	Chartwell Green (WGCHG)	