

# Specifications

technical identity\*

## Application

Sliding version:



Lift-slide version:



## Dimensions

Min. sightline 1-rail (fixed part)	50 mm
Min. sightline 1-rail (sliding part)	131 mm
Min. sightline 2-rail and 3-rail (sliding part)	131 mm
Min. sightline transom in vent	72 mm
Profile depth 1-rail	117,5 mm
Profile depth 2-rail	110,5 / 125 mm
Profile depth 3-rail	192 mm
Profile depth vent	50 mm

## Glazing

Infill thickness fixed parts 1-rail	2 - 35,5 mm
Infill thickness sliding parts 1-, 2-, 3-rail	2 - 35,5 mm
Glazing method:	dry glazed with EPDM gaskets or silicon
Gaskets	continuous gaskets

## Performance

Thermal break	24 mm polyamides PA 66 GF25 (18.6 mm in the vent)		
Forced entry resistance (burglary proof)	class 2	ENV 1627 – 1630	
<i>Sliding version:</i>			
Air permeability	4	600 Pa	EN 12207
Water tightness	7A	300 Pa	EN 12208
Wind resistance	C4	1 600 Pa, security 2400 Pa	EN 12210
<i>Lift-slide version:</i>			
Air permeability	4	600 Pa	EN 12207
Water tightness	8A	450 Pa	EN 12208
Wind resistance	C3	1 200 Pa, security 1 800 Pa	EN 12210

\*This information is only an indication. For more information, please consult your local Sapa Building System branch.