

Please Note: Use separate sheet for different colours

Order  Quote

Elite 63 Chamfered

With Glass  Unglazed

With Panels  No Panels

Company: \_\_\_\_\_ Customer Ref: \_\_\_\_\_

Office Use Only: Order No: \_\_\_\_\_ Order Date: / / Date Required: / /

Page \_\_\_ of \_\_\_

**(METRIC ONLY) VIEWED FROM INSIDE (INTERNALLY GLAZED ONLY)**

Frame Colour: \_\_\_\_\_ Window Handle Colour: \_\_\_\_\_ Door Handle Colour: \_\_\_\_\_

**Glass Specification** (28mm D/G as Standard)

Energy Grade: Float  Low E  <sup>STD</sup> Rating

Glazing: 28mm Double <sup>STD</sup> Triple  \_\_\_\_\_ mm

Spacer Bar: Bronze <sup>STD</sup> Warm Edge  Silver

\_\_\_\_\_  
Customer Signature

**Window Specification:** (Tick where applicable)

W Hardware: Espag <sup>STD</sup>  Twincam High Sec  Shoot Bolt High Sec

Trickle Vents(TV): No  Yes  <sup>Mark on each window</sup>

Window Drip: No <sup>STD</sup>  20mm  50mm\*

Handles Separate: Yes

**Door Specification:** (Tick where applicable)

D Hardware: 4 Roller <sup>STD</sup>  Hook Lock  Anti-Bump Cylinder

Doors Open: In  Out  <sup>STD</sup>

French Door: In  Out  <sup>STD</sup>

French Master: Left  Right

**1** Location: \_\_\_\_\_ Glass Type: \_\_\_\_\_ Opening Height: \_\_\_\_\_

Opening Width: \_\_\_\_\_

O/A Width: \_\_\_\_\_ O/A Height: \_\_\_\_\_

**2** Location: \_\_\_\_\_ Glass Type: \_\_\_\_\_ Opening Height: \_\_\_\_\_

Opening Width: \_\_\_\_\_

O/A Width: \_\_\_\_\_ O/A Height: \_\_\_\_\_

**3** Location: \_\_\_\_\_ Glass Type: \_\_\_\_\_ Opening Height: \_\_\_\_\_

Opening Width: \_\_\_\_\_

O/A Width: \_\_\_\_\_ O/A Height: \_\_\_\_\_

**4** Location: \_\_\_\_\_ Glass Type: \_\_\_\_\_ Opening Height: \_\_\_\_\_

Opening Width: \_\_\_\_\_

O/A Width: \_\_\_\_\_ O/A Height: \_\_\_\_\_

**5** Location: \_\_\_\_\_ Glass Type: \_\_\_\_\_ Opening Height: \_\_\_\_\_

Opening Width: \_\_\_\_\_

O/A Width: \_\_\_\_\_ O/A Height: \_\_\_\_\_

Sundries: \_\_\_\_\_

Location: **EXAMPLE** Glass Type: **CLEAR**

Opening Width: **1800mm** Opening Height: **1200mm**

620  
420  
20mm+ | OPENING | +20mm

O/A Width: **1840mm** O/A Height: **1240mm**

Special Instructions on how to allow for odd leg dimensions:

**\*\*For manufacturing sizes please add 20mm to your overall opening size for each Odd Leg required\*\***  
(See example)

Default Outer Frame Profiles for Odd Leg  
Windows: A10 & A11 (66mm)  
Open Out Doors: A12 & A13 (76mm)  
Open In Doors: A14 & A15 (110mm)  
(To allow for hinges)

**Panel | Composite Slab Details (Each)**

Box No	Colour In	Colour Out	Product Code	Glass Design	Backing Glass	Letterbox Colour	Knocker Type

Please Note: All of the following details are taken as standard unless specified by the customer.  
Manufacturing sizes only - Doors open outward as standard - Standard Drops: 420mm - Standard Width: 620mm - Fire Escape: 670mm - Door Mid Rail: 920mm